




XP-Q801 Thermal Receipt Printer

Exquisite design, easy to operate and maintain, help you save time and face different requirements from customers.

With high speed printing and reliable quality, long life and other excellent features make XP-Q801 become the best choice for some retail, hotels, catering, entertainment, health care, logistics and other industries.

Highlights

- Compatible with EPSON ESC/POS command
- Avoid order missing
- Support Linux
- Humanized design, easy to operate
- Fashionable modeling, perfect appearance



Avoid order missing



High printing speed



Support network printing



Support OPOS driver



Support GB18030

Key features

Easy to operate and open the cover, convenient for maintenance

Compact structure design, stable performance

High resolution printing



Specifications



MODEL	XP-Q801
Printing method	Direct thermal
Printing speed	200mm/s
Paper width	79.5 ± 0.5mm
Roll paper	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Line space	3.75mm (changeable using commands)
Interface	Serial+USB/Lan
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODABAR/ITF/CODE39/CODE93/CODE128
Extended characters	PC347 (Standard Europe) 、 Katakana、 PC850 (Multilingual) 、 PC860 (Portuguese) 、 PC863 (Canadian-French) 、 PC865 (Nordic) 、 West Europe、 Greek、 Hebrew、 East Europe、 Iran、 WPC1252、 PC866 (Cyrillic#2) 、 PC852 (Latin2) 、 PC858、 IranII、 Latvian、 Arabic、 PT151 (1251)
Auto cutter	Full/Partial(optional)
NV FLASH	256 K Bytes
Input buffer	64 K Bytes
Power supply	Input: AC 110V/220V, 50 ~ 60Hz
Power	DC 24V ---2.5A
Cash drawer control	DC 24V ---1A
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Operating environment	Win 9X/Win 2000/Win 2003/Win XP/Win 7/Win 8/Win 8.1/Linux
Print command	Compatible with ESC/POS
Gross weight	1.3 kg
Dimension	183 × 143.5 × 135mm (L × W × H)

